



Part Number	Drive Size	A inch/mm	B inch/mm	Penetration inch/mm	Part Number	Drive Size	A inch/mm	B inch/mm	Penetration inch/metric
RL5-1	T5	.059/1.49	.043/1.09	0.017/.43mm	RL27-1	T27	.200/5.09	.144/3.67	0.065/1.65mm
RL5-2	T5	.059/1.49	.043/1.09	0.025/.64mm	RL27-2	T27	.200/5.09	.144/3.67	0.075/1.90mm
RL5-3	T5	.059/1.49	.043/1.09	0.031/.79mm	RL27-3	T27	.200/5.09	.144/3.67	0.085/2.16mm
RL6-1	T6	.070/1.77	.050/1.29	0.022/.56mm	RL27-4	T27	.200/5.09	.144/3.67	0.090/2.29mm
RL6-2	T6	.070/1.77	.050/1.29	0.033/.84mm	RL27-5	T27	.200/5.09	.144/3.67	0.105/2.67mm
RL6-3	T6	.070/1.77	.050/1.29	0.041/1.04mm	RL27-6	T27	.200/5.09	.144/3.67	0.120/3.05mm
RL8-1	T8	.095/2.41	.069/1.75	0.038/.97mm	RL30-1	T30	.221/5.62	.160/4.06	0.055/1.40mm
RL8-2	T8	.095/2.41	.069/1.75	0.043/1.09mm	RL30-2	T30	.221/5.62	.160/4.06	0.070/1.78mm
RL8-3	T8	.095/2.41	.069/1.75	0.051/1.30mm	RL30-3	T30	.221/5.62	.160/4.06	0.075/1.90mm
RL10-1	T10	.111/2.81	.081/2.05	0.035/.89mm	RL30-4	T30	.221/5.62	.160/4.06	0.080/2.03mm
RL10-2	T10	.111/2.81	.081/2.05	0.040/1.02mm	RL30-5	T30	.221/5.62	.160/4.06	0.090/2.29mm
RL10-3	T10	.111/2.81	.081/2.05	0.045/1.14mm	RL30-6	T30	.221/5.62	.160/4.06	0.105/2.67mm
RL10-4	T10	.111/2.81	.081/2.05	0.050/1.27mm	RL30-7	T30	.221/5.62	.160/4.06	0.125/3.18mm
RL10-5	T10	.111/2.81	.081/2.05	0.060/1.52mm	RL40-1	T40	.267/6.78	.192/4.89	0.080/2.03mm
RL15-1	T15	.132/3.35	.096/2.43	0.033/.84mm	RL40-2	T40	.267/6.78	.192/4.89	0.090/2.27mm
RL15-2	T15	.132/3.35	.096/2.43	0.041/1.04mm	RL40-3	T40	.267/6.78	.192/4.89	0.097/2.46mm
RL15-3	T15	.132/3.35	.096/2.43	0.045/1.14mm	RL40-4	T40	.267/6.78	.192/4.89	0.110/2.79mm
RL15-4	T15	.132/3.35	.096/2.43	0.050/1.27mm	RL40-5	T40	.267/6.78	.192/4.89	0.135/3.42mm
RL15-5	T15	.132/3.35	.096/2.43	0.060/1.52mm	RL45-1	T45	.313/7.95	.224/5.68	0.110/2.79mm
RL15-6	T15	.132/3.35	.096/2.43	0.070/1.78mm	RL45-2	T45	.313/7.95	.224/5.68	0.115/2.92mm
RL20-1	T20	.155/3.93	.112/2.85	0.038/.97mm	RL45-3	T45	.313/7.95	.224/5.68	0.125/3.18mm
RL20-2	T20	.155/3.93	.112/2.85	0.050/1.27mm	RL45-4	T45	.313/7.95	.224/5.68	0.140/3.56mm
RL20-3	T20	.155/3.93	.112/2.85	0.056/1.42mm	RL45-5	T45	.313/7.95	.224/5.68	0.155/3.94mm
RL20-4	T20	.155/3.93	.112/2.85	0.060/1.52mm	RL50-1	T50	.353/8.96	.256/6.50	0.110/2.79mm
RL20-5	T20	.155/3.93	.112/2.85	0.065/1.65mm	RL50-2	T50	.353/8.96	.256/6.50	0.129/3.28mm
RL20-6	T20	.155/3.93	.112/2.85	0.080/2.03mm	RL50-3	T50	.353/8.96	.256/6.50	0.143/3.63mm
RL20-7	T20	.155/3.93	.112/2.85	0.089/2.26mm	RL50-4	T50	.353/8.96	.256/6.50	0.154/3.91mm
RL25-1	T25	.178/4.53	.129/3.27	0.055/1.40mm	RL50-5	T50	.353/8.96	.256/6.50	0.176/4.47mm
RL25-2	T25	.178/4.53	.129/3.27	0.060/1.52mm	RL55-1	T55	.447/11.35	.318/8.09	.115/2.92mm
RL25-3	T25	.178/4.53	.129/3.27	0.065/1.65mm	RL55-2	T55	.447/11.35	.318/8.09	.135/3.43mm
RL25-4	T25	.178/4.53	.129/3.27	0.075/1.90mm	RL55-3	T55	.447/11.35	.318/8.09	.155/3.94mm
RL25-5	T25	.178/4.53	.129/3.27	0.090/2.29mm	RL55-4	T55	.447/11.35	.318/8.09	.175/4.45mm
RL25-6	T25	.178/4.53	.129/3.27	0.115/2.92mm	RL55-5	T55	.447/11.35	.318/8.09	.215/5.46mm

1. Punch Pin materials:

- M2 at RC 61-64
- M42 at RC 63-65
- Carbide: D60 and D70 available. Specify when ordering

2. Special penetrations available. Specify required penetration when ordering.

3. Oversize pins available for heavy plating or hot heading applications.

4. PVD Coatings available for cold & hot heading applications.