



Tamper Resistant

Part Number	Drive Size	A inch/mm	B inch/mm	Penetration inch/mm	Part Number	Drive Size	A inch/mm	B inch/mm	Penetration inch/mm
8PLI-634	8IP	.094/2.39	.068/1.73	.030/.76	27PLI-634	27IP	.201/5.11	.146/3.71	.064/1.13
8PLI-633	8IP	.094/2.39	.068/1.73	.035/.89	27PLI-633	27IP	.201/5.11	.146/3.71	.074/1.88
8PLI-632	8IP	.094/2.39	.068/1.73	.040/1.02	27PLI-632	27IP	.201/5.11	.146/3.71	.084/2.13
9PLI-634	9IP	.102/2.59	.074/1.88	.033/.84	30PLI-634	30IP	.220/5.59	.161/4.09	.070/1.78
9PLI-633	9IP	.102/2.59	.074/1.88	.038/.97	30PLI-633	30IP	.220/5.59	.161/4.09	.082/2.08
9PLI-632	9IP	.102/2.59	.074/1.88	.043/1.09	30PLI-632	30IP	.220/5.59	.161/4.09	.093/2.36
10PLI-634	10IP	.111/2.82	.081/2.06	.035/.89	40PLI-634	40IP	.267/6.78	.194/4.93	.085/2.16
10PLI-633	10IP	.111/2.82	.081/2.06	.041/1.04	40PLI-633	40IP	.267/6.78	.194/4.93	.098/2.49
10PLI-632	10IP	.111/2.82	.081/2.06	.046/1.17	40PLI-632	40IP	.267/6.78	.194/4.93	.112/2.84
15PLI-634	15IP	.132/3.35	.096/2.44	.042/1.07	45PLI-634	45IP	.313/7.95	.227/5.77	.100/2.54
15PLI-633	15IP	.132/3.35	.096/2.44	.049/1.24	45PLI-633	45IP	.313/7.95	.227/5.77	.115/2.92
15PLI-632	15IP	.132/3.35	.096/2.44	.055/1.40	45PLI-632	45IP	.313/7.95	.227/5.77	.131/3.33
20PLI-634	20IP	.155/3.94	.113/2.87	.049/1.24	50PLI-634	50IP	.353/8.97	.256/6.50	.112/2.85
20PLI-633	20IP	.155/3.94	.113/2.87	.057/1.45	50PLI-633	50IP	.353/8.97	.256/6.50	.130/3.81
20PLI-632	20IP	.155/3.94	.113/2.87	.065/1.65	50PLI-632	50IP	.353/8.97	.256/6.50	.148/3.76
25PLI-634	25IP	.179/4.55	.130/3.30	.057/1.45	55PLI-634	55IP	.448/11.38	.325/8.26	.142/3.61
25PLI-633	25IP	.179/4.55	.130/3.30	.066/1.68	55PLI-633	55IP	.448/11.38	.325/8.26	.164/4.17
25PLI-632	25IP	.179/4.55	.130/3.30	.057/ 1.45	55PLI-632	55IP	.448/11.38	.325/8.26	.187/4.75

1. Punch Pin materials:

- M2 at 61-64 RC.
- M42 at RC 63-65

2. Special penetrations available. Specify required penetration when ordering.

3. PVD Coatings available for cold & hot heading applications.